



AIC0101



GAS OVEN 6 TRAYS 600 x 400 - GN 1/1
MECHANICAL CONTROL



FUNCTIONAL CHARACTERISTICS

Display	Analogic
Supply	Natural gas / GPL
Timer	Linear scale
Number of motors	2
Motor speeds	2
Max cooking temperature	260 [°C] 500 [°F]
Core probe	-
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50 [mm] open 2 [inch] open
Humidification	Direct Injection
Air Injection	-
Version	Standard

STANDARDS

Certification	CE-GAR-CB
---------------	-----------

TRAYS

Trays rack	Wire PA-BIV 6/80 [mm] Wire PA-BIV 6/3,14 [inch] Sheet PA 6/85 [mm] Sheet PA 6/3,34 [inch]
Max tray load	4 [kg] 9 [lb]

DIMENSIONS

Oven size with handle WxDxH (mm)	939x933x986 [mm] 37x36,7x38,9 [inch]
Oven size without handle WxDxH (mm)	939x868x986 [mm] 37x34,2x38,9 [inch]
Chamber size WxDxH (mm)	660x486x489 [mm] 26x19,1x19,2 [inch]
Unit weight (Kg)	129 [kg] 284 [lb]

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	1020x970x1082 [mm] 40,1x38,2x42,5 [inch]

Unit weight with packaging (Kg)	150 [kg] 330 [lb]
Crate packaging size (optional)	-
ELECTRICAL DATA	
50Hz	
Power	0,58 kW
Frequency	50Hz
Power supply	220-240V 1N~
Amperage	2,6A
Power cord req.	3G1,5
60Hz	
Power	0,58 kW
Frequency	60Hz
Power supply	220-240V 1N~
Amperage	2,6A
Power cord req.	3G1,5
BURNER DATA	
G30-G31 Power (kW)	15
G20 Power (kW)	15
WATER CONNECTION REQUIREMENTS	
Humidification Water Inlet	3/4" M Gas threaded
Washing Water Inlet	8 [mm] quick fitting
Water drain	30 [mm] 1,2 [inch]
Max water hardness	5 [°f]
Water pressure requirement min-max	150-200 [kPa] 22-29 [psi]
CONSUMPTION	
Humidification Water (L/h)	22,4 [l/h] max consumption 5,9 [gal/h] max consumption
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

CONNECTIVITY	
USB	USB 2.0
Bluetooth	-
Wi-Fi	Yes
Cloud	Yes
ACCESSORIES	
Nozzle kit	85BRU00018 (GAS02)
Self clean system kit	-
Oven stand	TA9374H30X TA9374H40X-TA9374H40S TA9374H49X-TA9374H49S TA9374H70X-TA9374H70S TA9374H80X-TA9374H80S
Hood (Air)	-
Hood (Water)	-
Core probe	CP1
Proofer	CA9308M0 CA9308MH CA9308DH
Stacking kit for 2 ovens	-
Smoker	SMK02
Blast chiller	KDA03 KDA05
Blast chiller stacking kit	SK43
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S4
Detergent 6KG	DT2
Detergent 10KG	DT4